

ROHS Compliant

DATE	2022/06/20
Revision	C

Features :

- T-568A/B Dual wiring
- RJ45 complies with FCC part 68 standard
- 110/Krone dual IDC connector compatible
- Provides termination for 22~26 AWG wire
- Jack insertion life >750 mating cycles
- IDC insertion life >250 mating cycles
- Operating temperature : -40°C ~ +60°C

Electrical :

- Contact resistance : 20m ohm
- DC Current rating : 1.5Amps
- DC resistance : Max.0.1 ohm
- Insulation Resistance : 500m ohm
- Dielectric withstanding voltage : 1000V

TOLERANCE

.XXX	0.10
.XX	0.25
.X	0.38

MATERIAL

CATEGORY  CAT.5E  CAT.6  CAT.3  OTHER \_\_\_\_\_

FRAME METALLIC SPCC + PC

IDC PLASTIC PC, UL 94-V0

IDC CONTACT PHOSPHOR BRONZE WITH 200U" TIN OVER NICKEL

CONTACT 0.35 mm DIAMETER PHOSPHOR BRONZE GOLD PLATED OVER NICKEL

GOLD-PLATING  0.0762 um / 3u inch  0.15 um / 6u inch  0.38 um / 15u inch  0.76 um / 30u inch  1.27 um / 50u inch

TYPE OF PRODUCT  UNSHIELD  SHIELD : STAINLESS COVER

P/NO. SY-509-50

ITEM. Patch Panel

CO. SY

S/N. SY-509-50

DR.

APPD. Sweet 2022/06/20

CHKD.

Shiunn Yang Ent.Co.Ltd.  
TEL: 29089890 <REP>  
FAX: 29068849,29088679

FILE. SY-509-50

SCALE /

UNIT mm SIZE A4